

# DLF grey/white

## DLF 76 (3") & 130 (5")

- Packaging : 9x50 for 5" & 25x60 for 3" size
- Composition Fiber : 100% Rayon Fiber with resin
- Composition Jersey: With or without loop pile available
- Color Fiber : Grey backing on White Polishing side
- Color Jersey : Bottle Green or Black

## Physical characteristics

Tests	Measures	Results	Targets	Methods
Diameter	mm	76 & 130	76 & 130	
Thickness	mm	5.5	5	ERT 30.4-89
Weight	g/M <sup>2</sup>	710	720	ERT 40.3-90
Pore volume	%	89	89	
Density	g/cm <sup>3</sup>	0.14	0.14	DIN EN ISO 845
Abrasion resistance	# Turns	5000	5000	Martindale Test
Thermal Shrinkage	at 70°C	max 1%	max 1%	DIN EN ISO 3386-1
Tensile Strength	kPa	1200	1200	DIN EN ISO 1798

## Applications

- High resistant Rayon fiber ensure high gloss finish of various surfaces such as Minerals, Plastics, Plexi, Acryl, Glass and Coatings
- High Cutting Power with good finish and min. heat production to shorten Processtime and obtain fast gloss, stable process.
- Fast exchange of pad with loop pile or also available without loop pile fabric , saves time and money
- Good fixation ensures a stable position , no lint so no contamination
- Fibers are fixed with resin binders for high duration guarantee and controlled hardness