

## Buffing Pad DLX White Soft

- Reference : **DLX 76 (3") & 130 (5")**
- Packaging : **9x50 for 5" & 25x60 for 3" size**
- Usage area : **Worldwide OEM and After Market usage**
- Fiber Composition : **100% Polyester Fiber without resin**
- Jersey Loop Pile Composition : **Black "Walloo" Polyester**
- Color Fiber of the Pad : **White**
- Color Jersey Loop pile : **Black "Walloo"**

## Physical properties

Tests	Measure	Result	Spec Targets	Methods
Diameter	mm	76 & 130	76 & 130	
Thickness	mm	4.5	4.5	ERT 30.4-89
Weight	g	510	500	ERT 40.3-90
Pore volume	%	90	90	
Density	g/cm <sup>3</sup>	0.1	0.1	DIN EN ISO 845
Abrasion resistance	# turns	3500	3000	Martindale Test
Thermal shrinkage	at 70 ° C	max1%	max1%	DIN EN ISO 3386-1
Tensile strength	kPa	1300	1300	DIN EN ISO 1798

## Applications

- Softer Polyester fiber ensure high gloss finish of various surfaces such as Minerals, Plastics, Plexi, Acryl, Glass and Coatings
- Soft Cutting Power with good finish and min. heat production to shorten Processtime and obtainfast gloss, stable process.
- Fast exchange of pad with loop pile or also available without loop pile fabric , saves time and money
- Good fixation ensures a stable position , no lint so no contamination
- No foreign fibers or binders ensure a constant finish and a soft treatment of the delicate surface
- Needle punched and Thermobonded fibers guarantee a high duration and controlled hardness for equal polishing result