

Buffing / Polishing Pads PDM AU

- Reference : **9DLPDM-AU-76VBN (3")** or **9DLPDM-AU-130VBN(5")**
- Packaging : **300 (5") Single packed** or **1000 (3") in bags of 12**
- Document name : **Norme E32.90.025.G**
- Fiber Composition : **100% Virgin Wool AU quality**
- Jersey Loop Pile Composition : **100% Polyester**
- Color Fiber of the Pad : **Naturel**
- Color Jersey Loop pile : **Bottle Green**

Physical characteristics

Tests	Measures	Results	Targets	Methods
Diameter	mm	76/130/150	76/130/150	
Thickness	mm	18	18	
Weight	g/M ²	10/34/39	approx weight	natural lambswool variances
Jersey Loop Pile Adhesion strength	N/cm	Stitched	Stitched	
Tear Resistance New	N/m	12	11	D41 1049
Tear resistance after 7 days at 70°C	N/m	12	11	D41 1049
Elongation to break new	%	15	13	D41 1050
Elongation to break after 7 days at 70°C	%	15	13	D41 1050
Tensile Strength	kPa	600	600	DIN EN ISO 1798
Elongation at break	%	50	50	DIN EN ISO 1798

Packaging Finished Product

Case size	48x48x48 cm
Case weight 3" - 1000 Units/case	12,5 Kg Gross weight
Case weight 5" - 300 Units/case	12 Kg Gross weight

Applications

- Natural Lambswool fiber ensure high resistance during usage
- Special glue and stitching technology ensures permanent fix of the pad onto the attachment loop pile velours
- Available in various sizes with velcro attachment system or with string.